



HD80IRM

Night Vision HD Indoor/Outdoor IP Dome Camera





3MP High Definition for professional quality detail



With Power over Ethernet, both video and power travel along one cable



True Day / Night capability for 24-hour surveillance



IP66 rated construction to withstand tough weather conditions for outdoor installation



Digital Wide Dynamic Range (D-WDR) provides superior image clarity in drastic lighting conditions




Dual Streaming allows simultaneous H.264 transmission




HD **P**

HD80IRM

Night Vision HD Indoor/Outdoor IP Dome Camera





Camera Specifications	
Model	HD80IRM
Resolution	3MP
Image Sensor	High Resolution Sony CMOS
Wide Dynamic Range	Digital Wide Dynamic Range
Focal Length	3 ~ 9 mm Autofocus
FOV	32° ~ 96.1°
Iris Control	Auto Iris
Backlight Compensation	Yes
Auto Gain Control	Yes
Minimum Illumination	0 Lux w/ IR LED
Day / Night	True Day / Night with IR Cut Filter
IR LEDs	24
IR Range	60 ft (20 m)
Auto White Balance Range	2700K ~ 8000K
Compression	H.264
Input Voltage	PoE Only IEEE 802.3af Power over Ethernet 48vDC
Power Consumption	9.3W
IP Rating	IP66
Heater	No
Operating Temperature	18° ~ 118°F (-8° ~ 48°C)
Dimensions	4.6" x 3.6" (116.84 x 91.44 mm)
Weight	0.6 lbs (280g)



1-855-2avertX (1-855-228-3789)

www.avertx.com

32352AC

Copyright © 2014 AvertX. All rights reserved. Information contained in this document is subject to change without prior notice. AvertX does its best to provide accurate information, but cannot be held responsible for typos or mistakes.